₫

more products please

# Our Product Introduction

# Automatic Packing Plastic Electric Strapping Tool Rechargeable Bander Wrapping Machine

### Basic Information

Place of Origin: China
Brand Name: Zhuoyu
Certification: CE
Model Number: V2
Minimum Order Quantity: 1 set

• Price: To be discussed

• Packaging Details: 440\*290\*190mm for one set per box

• Delivery Time: 10-15 work days

• Payment Terms: L/C, D/A, D/P, T/T, Western Union,

MoneyGram

• Supply Ability: 1000 box per 10days



# Product Specification

Features: Automatic Tensioning, Adjustable Tension
 Force One button Operation Expenses

Force, One-button Operation, Ergonomic Design, Low Noise, High Efficiency

Sealing Method: Friction Welding
 Power Source: Electric
 Battery Capacity: 4.0Ah

Battery Capacity: 4.0AhStrap Width: 13-16mmTensioning Force: 900-32000N

• Dimensions: 380mm X 130mm X 130mm

• Weight: 3.58kg

Highlight: Automatic Packing Electric Strapping Tool,
 Rechargeable Electric Strapping Tool,

Rechargeable electric bander tool



### More Images









### Product Description

# DESCRIPTION

The V2 strapping tool is equipped with an easy to operate touch screen, located always insight of the operator. Clear

to read symbols make that everybody can work Smart with it. This unique 3-in-1 tool combines Manual, Semi-

Automatic or Automatic operation in one tool, by simply selecting the mode you want to use. Without changing the

No more mechanical buttons. The slanted placed touch screen, with its flat outlet at the bottom, prevents water and dust from entering the device here, extending service life dramatically .

Consistent and reliable performance – with teach-in mode – by easy setting and locking of the right tension force, speed and sealing time at the touch of a finger. This one-handed operation tool allows you to consistently strap a great variety of products, in series or individual and variable packages.

Tested to endure, the V2 has passed several severe quality endurance tests to meet and exceed the demanding quality requirements and customer demand. Very high capacity of up to 600 strap cycles per battery load (dependent on strap quality and dimension)

TECHNI	CAL
LCIN	0, 1

Polyester (PET) and Polypropylene (PP) plain and embossed	

ㅈ
ᅙ
$\neg$
굶
$\simeq$
Ф
$\overline{}$
3
9
$\simeq$
≒
- 23
S
O
ਜ਼
ã
ŝ
Φ
<
S
ISI
S
no su
ĭ
-
ĕ
ĕ
≒
ಕ
മ്
ଚ
~
om
3

Strapping Dimensions	width 13.0 – 16.0 mm / ½ - 5%" thickness 0.40 – 1.20 mm / .016 – .047"	ZHUOYU Manada Manada Ma	Anhui Zhuoyu Industrial Manufacture Co., Ltd.
Weight incl. 4.0 Ah battery	3.58KG/7.89lbs	_	
Tool size with 4.0 Ah battery	L380 x W130 x H130 mm / 13.8 x 5.3 x 5.6"	<b>3</b>	e setuopack.com
Type of seal	Friction welding	D 404 4-45	7
Average seal strength	approx. 75% (dependent on the strap quality)	Ruilding A3 Innov	vation
Tension force	900 - 3200 N / 202 - 720 lbs (adjustable)	industrial Park.	800
Tension speed	49 - 174 mm/s / 1.9 - 6.8 inch/s	Wangjiang WestF	Road,
Power supply	Battery Li-Ion 16.8-21 VDC / 4.0 Ah	High-tech Zone, F	
		Anhui, China	l.