

High Tension Pneumatic Strapping Tool Alloy Ash Baler Tensioner OEM

Our Product Introduction

for more products please visit us on setuopack.com

Basic Information

• Place of Origin:

• Brand Name:

• Certification:

Model Number:

• Woder Number.	BQD23	
Minimum Order Quantity:	1 stage	
Price:	To be discussed	
 Packaging Details: 	375*230*200mm	
 Delivery Time: 	10-15 work days	
• Payment Terms:	MoneyGram, Western Union, T/T, D/P, D/A, L/C	
 Supply Ability: 	100+box+10days	
Product Specification		
 Model: 	BQD25	
Applicable Strapping Tape Width:	19-25mm	
Applicable Strapping Tape Tickness:	0.5-1.5mm	
Air Pressure:	0.5-0.8Mpa	
 Applicable Straps Type: 	PET/PPStraps	
 Enter Strap Modle: 	Free Tape	
 Strap Sealing Form: 	Friction Welding	
 Maximum Binding Force: 	4500N	
Net Weight(N.W.):	3.8kg	
• Size:	280*160*180mm	
Highlight:	High Tension Pneumatic Strapping Tool,	

China

Zhuoyu

CE BOD25

High Tension Pneumatic Strapping Tool, Pneumatic Strapping Tool Alloy Ash Baler, OEM pneumatic tensioner





More Images



Product Description

BQD25 pneumatic packaging machine

it away.

Our Product Introduction

BQD25 pneumatic strapping machine is a pneumatic strapping tool with the characteristics of light weight, easy operation, safety and reliability, fast and firm strapping, and low labor intensity. It is suitable for strapping steel, pipes, plates, brick factories, and other objects. This machine uses compressed air as the power source, which has excellent bundling effect and is safe, efficient, time-saving, and labor-saving, effectively improving work efficiency. Easy to operate, portable operation, no need for packaging buckle, can complete the work by tightening the fusion cutting belt. It has a lightweight body: the body is lightweight and flexible to use; Portable handheld design, just lift it up and take

Strong safety: evenly tied; Automatic bundling to prevent accidental operation by personnel. Its characteristic is that it does not require upper and lower packaging straps, saving a lot of time and cost.

Applicable Strapping Tape Width	19-25mm
indexers strated indexers	

for
mor
ore
products
please
visit us
sn
g
setu
lopa
ÖK.
oom

Applicable Strapping Tape Tickness	0.5-1.5mm
Air Pressure	0.5-0.8Mpa
Applicable straps Type	PET/PP Straps
Enter Strap Modle	Free tape
Strap Sealing Form	Friction Welding
Maximum Binding Force	4500N
Net Weight(N.W.)	3.8kg
Size	280*160*180mm

Anhui Zhuoyu Industrial Manufacture Co., Ltd.

S Setuopack.com

Room 101, 1st Floor, Building A3, Innovation industrial Park, 800 Wangjiang WestRoad, High-tech Zone, Hefei, Anhui, China.