

## OEM Polyester Poly Strapping Metal Seals Packaging Buckle 50mm

Our Product Introduction

for more products please visit us on [setuopack.com](http://setuopack.com)

### Basic Information

- Place of Origin: China
- Brand Name: Zhuoyu
- Certification: CE
- Model Number: P0.9\*25\*50
- Minimum Order Quantity: 18kg
- Price: To be discussed
- Delivery Time: 10-15 work days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 100+box+10days




### Product Specification

- Length: 50mm
- Width: 25mm
- Thickness: 0.9mm
- Lock Buckle Strength: Rm700MPa
- Surface: Cold Rolling
- Weight: 18kg
- Highlight: OEM poly strapping metal seals, 50mm poly strapping metal seals, OEM polyester strapping seals



### More Images



### Product Description

#### Closed lock buckle

Packaging buckle is a product widely used in packaging, logistics, manufacturing and other industries. It is mainly used to fix and tighten steel belts, or other types of packing belts, thus ensuring the stability and safety of goods during transportation and storage.

Packaging buckle with high connection strength and impact resistance, usually made of high-strength material, so that it can withstand large tensile and impact force, not easy to break or deformation.

After the entire packing process is completed, the packing buckle and the steel belt will together form a strong packaging structure to ensure the stability of the goods during transportation and storage.

Packaging buckle, the surface of the cold rolling treatment, this treatment can enhance its surface hardness and wear resistance, thereby extending the service life. At the same time, its strength reaches Rm700MPa, showing extremely high tensile strength and impact resistance, ensuring that it can withstand large external forces and is not easy to damage during the packaging process.

With 25mm wide steel belt, this width of steel belt is more common in the packaging industry, it is suitable for pneumatic baler, the packaging buckle and the use of pneumatic baler, can achieve fast and reliable packaging operation. During the packing process, the packing buckle can firmly lock the steel belt to ensure the stability and safety of the goods during transportation and storage. At the same time, the use of pneumatic baling machine also

Our Product Introduction

for more products please visit us on [setuopack.com](http://setuopack.com)

greatly reduces the labor intensity of the operator and improves the work efficiency.

length	50mm
width	25mm
thickness	0.9mm
Lock buckle strength	Rm700MPA
surface	cold rolling
weight	18kg
Applicable steel strip	Roasted blue,Black paint



Anhui Zhuoyu Industrial Manufacture Co., Ltd.



[setuopack.com](http://setuopack.com)

Room 101, 1st Floor, Building A3, Innovation industrial Park, 800 Wangjiang WestRoad, High-tech Zone, Hefei, Anhui, China.