


Closed Type Poly 3/4 Steel Strapping Seals Cold Galvanized Packaging Lock Buckle

Our Product Introduction

for more products please visit us on setuopack.com


Basic Information

- Place of Origin: China
- Brand Name: Zhuoyu
- Certification: CE
- Model Number: P0.9*32*50Z
- Minimum Order Quantity: 25kg
- Price: To be discussed
- Delivery Time: 10-15 work days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 100+box+10days



Product Specification

- Length: 50mm
- Width: 32mm
- Thickness: 0.9mm
- Lock Buckle Strength: Rm700MPA
- Surface: Cold Galvanizing
- Weight: 25kg
- Highlight: Closed Type 3 4 steel strapping seals, Galvanized 3 4 steel strapping seals, Packaging poly strapping seals



More Images



Product Description

Closed lock buckle

Packaging buckle is a product widely used in packaging, logistics, manufacturing and other industries. It is mainly used to fix and tighten steel belts, or other types of packing belts, thus ensuring the stability and safety of goods during transportation and storage. Packaging buckle with high connection strength and impact resistance, usually made of high-strength material, so that it can withstand large tensile and impact force, not easy to break or deformation.

After the entire packing process is completed, the packing buckle and the steel belt will together form a strong packaging structure to ensure the stability of the goods during transportation and storage.

Its surface is treated with cold galvanizing, which can enhance its surface hardness and wear resistance, thereby extending its service life. At the same time, its strength reaches Rm700MPa, demonstrating extremely high tensile strength and impact resistance, ensuring that it can withstand large external forces during the packaging process without being easily damaged.

With 32mm wide steel belt, this width of steel belt is more common in the packaging industry, it is suitable for pneumatic baler, the packaging buckle and the use of pneumatic baler, can achieve fast and reliable packaging operation. During the packing process, the packing buckle can firmly lock the steel belt to ensure the stability and safety of the goods during transportation and storage. At the same time, the use of pneumatic baling machine also greatly reduces the labor intensity of the operator and improves the work efficiency.

for more products please visit us on setuopack.com

length	50mm
width	32mm
thickness	0.9mm
Lock buckle strength	Rm700MPA
surface	Cold galvanizing
weight	25kg
Applicable steel strip	Roasted blue,Black paint,Hot dip galvanizing



Anhui Zhuoyu Industrial Manufacture Co., Ltd.



setuopack.com

Room 101, 1st Floor, Building A3, Innovation industrial Park, 800 Wangjiang WestRoad, High-tech Zone, Hefei, Anhui, China.