

Closed Lock Poly Metal Steel Strapping Seals Packaging Buckle 32mm 0.9mm Thickness

Our Product Introduction

for more products please visit us on setuopack.com

Basic Information

- Place of Origin: China
- Brand Name: Zhuoyu
- Certification: CE
- Model Number: P0.9*32*50Z
- Minimum Order Quantity: 25kg
- Price: To be discussed
- Delivery Time: 10-15 work days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 100+box+10days



Product Specification

- Length: 50mm
- Width: 32mm
- Thickness: 0.9mm
- Lock Buckle Strength: Rm450MPa
- Surface: Hot Dip Galvanizing
- Weight: 25kg
- Highlight: Packaging Steel Strapping Seals, 32mm Steel Strapping Seals, Packaging poly strapping metal seals



More Images



Product Description

Hot dip galvanized locking buckle

The packing buckle is mainly used for fixing and steel straps to ensure the stability and safety of goods during transportation and storage.

The packaging buckle has high connection strength and impact resistance, and is usually made of high-strength materials, which can withstand large tensile and impact forces and is not easy to break or deform.

Its surface has undergone hot-dip galvanizing treatment, which can improve its surface hardness and wear resistance, thereby extending its service life. At the same time, its strength reaches Rm450MPa, demonstrating extremely high tensile strength and impact resistance, ensuring that it can withstand large external forces during the packaging process without being easily damaged.

When paired with a 32mm wide baked blue and painted steel strip, it can be used in pneumatic packaging machines. When used in conjunction with pneumatic packaging machines, this type of packaging buckle can achieve fast and reliable packaging operations. When using a 32mm wide hot-dip galvanized steel strip, it can be suitable for manual packaging machines, which can save energy.

length	50mm
--------	------

Our Product Introduction

for more products please visit us on setupack.com

width	32mm
thickness	0.9mm
Lock buckle strength	Rm450MPA
surface	Hot dip galvanizing
weight	25kg
Applicable steel strip	Roasted blue,Black paint,Hot dip galvanizing



Anhui Zhuoyu Industrial Manufacture Co., Ltd.



setupack.com

Room 101, 1st Floor, Building A3, Innovation industrial Park, 800 Wangjiang WestRoad, High-tech Zone, Hefei, Anhui, China.