₫

# Mechanical Split Steel Pneumatic Strapping Tensioner Baler 25mm

### **Basic Information**

Place of Origin: China
Brand Name: Zhuoyu
Certification: CE
Model Number: FTL/S25
Minimum Order Quantity: 1 set

Price: To be discussed Delivery Time: 10-15 work days

Payment Terms:
 L/C, D/A, D/P, T/T, Western Union, MoneyGram

• Supply Ability: 100+box+10days



# Product Specification

 Features: Pneumatic Operation, Adjustable Tensioning Force, Durable Steel Construction

Strap Width: 13-19mm

Safety Features: Built-in Safety Mechanism To Prevent Over-

tensioning

Accessories: Comes With A Set Of Replacement Parts

And Tools For Maintenance And Repairs

Weight: 3.8kgMaterial: SteelStrap Thickness: 0.5-1.5mm

Maintenance: Regular Maintenance And Lubrication

Required For Optimal Performance

• Tensioning Force: 2000N

Ease Of Use: Ergonomic Design For Easy Handling And

Operation

Compatibility: Compatible With Steel Strapping Of Various

Widths And Thicknesses



### More Images





## Product Description

# Pneumatic tensioner

Split pneumatic baler, usually composed of tensioning machine and locking machine, is a kind of mechanical equipment widely used in various goods packaging fields. The following is a detailed introduction to the split pneumatic baler (tensioner and latching machine):

First, the tension machine part

The tensioner creates a strong pull force through a pneumatic system that tightly wraps the steel strip around the cargo.

The user can adjust the tension of the tensioner according to the actual situation of the goods to ensure the firmness of the packaging.

Second, the locking machine part

After the steel belt is tightened, the locking machine fixes the buckle on the steel belt or plastic steel belt to prevent it from loosening or falling off.

Improve packaging efficiency: The automatic operation of the locking machine can greatly shorten the packaging time and improve the packaging efficiency.

To sum up, the split pneumatic baler is an efficient and reliable cargo packaging equipment. Through the combination

# for more products please visit us on setuopack.com

of the tension machine and the locking machine, the goods can be quickly packed and firmly fixed.

specification	25mm
use air pressure	0.49-0.63Mpa
Strip width	0.6-1.2mm
Tension Force	8.5N
Net weight (m.w.)	7.2kg

Anhui Zhuoyu Industrial Manufacture Co., Ltd.





e setuopack.com

Room 101, 1st Floor, Building A3, Innovation industrial Park, 800 Wangjiang WestRoad, High-tech Zone, Hefei, Anhui, China.