Split Type Pneumatic Strapping Tensioner Baler Steel Banding Tool For 19mm Steel Belt

Basic Information

Place of Origin: China
Brand Name: Zhuoyu
Certification: CE
Model Number: FTL/S19
Minimum Order Quantity: 1 set

Price: To be discussed Delivery Time: 10-15 work days

Payment Terms:
 L/C, D/A, D/P, T/T, Western Union, MoneyGram

• Supply Ability: 100+box+10days



Product Specification

Tensioning Force: Up To 900 Lbs
Material: Steel
Air Pressure: 70-100 Psi

Usage: Industrial Packaging And Shipping
 Suitable For: Heavy Duty Strapping Applications

Strap Width: 1/2 Inch

Dimensions: 14.5 X 6.5 X 5 Inches
Strap Thickness: 0.015-0.035 Inch
Tensioning Method: Pneumatic
Weight: 6.5 Lbs

Strap Type: Polyester Or Polypropylene

• Air Consumption: 4.5 CFM

Highlight: Split Type Pneumatic Strapping Tensioner,
 Steel Banding Pneumatic Strapping Tensioner,

19mm pneumatic steel banding tool



More Images







Product Description

Pneumatic tensioner

Split pneumatic baler, usually composed of tensioning machine and locking machine, is a kind of mechanical equipment widely used in various goods packaging fields. The following is a detailed introduction to the split pneumatic baler (tensioner and latching machine):

First, the tension machine part

The tensioner creates a strong pull force through a pneumatic system that tightly wraps the steel strip around the cargo.

The user can adjust the tension of the tensioner according to the actual situation of the goods to ensure the firmness of the packaging.

Second, the locking machine part

After the steel belt is tightened, the locking machine fixes the buckle on the steel belt or plastic steel belt to prevent it from loosening or falling off.

Improve packaging efficiency: The automatic operation of the locking machine can greatly shorten the packaging time and improve the packaging efficiency.

To sum up, the split pneumatic baler is an efficient and reliable cargo packaging equipment. Through the combination

for more products please visit us on setuopack.com

of the tension machine and the locking machine, the goods can be quickly packed and firmly fixed.

specification	19mm
use air pressure	0.49-0.63Mpa
Strip width	0.6-1.2mm
Tension Force	8.5N
Net weight (m.w.)	7.2kg

Anhui Zhuoyu Industrial Manufacture Co., Ltd.





e setuopack.com

Room 101, 1st Floor, Building A3, Innovation industrial Park, 800 Wangjiang WestRoad, High-tech Zone, Hefei, Anhui, China.