

A19 Portable Pneumatic Plastic Steel Belt Baler High Tensile Force 3500N Hot Melt Free

Our Product Introduction

for more products please visit us on setupack.com

Basic Information

- Place of Origin: China
- Brand Name: Zhuoyu
- Certification: CE
- Model Number: A19
- Minimum Order Quantity: 1 stage
- Price: To be discussed
- Packaging Details: 375*230*200mm
- Delivery Time: 10-15 work days
- Payment Terms: MoneyGram, Western Union, T/T, D/P, D/A, L/C
- Supply Ability: 100+box+10days




Product Specification

- Model: A19
- Applicable Strapping Tape Width: 13-19mm
- Applicable Strapping Tape Thickness: 0.5-1.5mm
- Air Pressure: 0.5-0.8Mpa
- Applicable Straps Type: PET/PPStraps
- Enter Strap Mode: Divided Up And Down
- Strap Sealing Form: Friction Welding
- Maximum Binding Force: 3500N
- Net Weight(N.W.): 3.8kg
- Size: 280*160*180mm
- Highlight: 3500N pneumatic plastic steel belt baler, Portable Plastic Steel Belt Baler



More Images



Product Description

A19 Pneumatic plastic steel belt baler

The A19 pneumatic plastic steel belt baler is the ideal choice for your packing job with its excellent performance and wide applicability.

High tensile design: The machine has a strong pulling force of 3500N, which can easily cope with the packaging needs of various heavy items, ensuring the firmness and stability of the packaging.

Plastic steel belt applicability: suitable for the width between 13-19mm, thickness in the range of 0.5-1.5mm plastic steel belt, to provide you with a variety of options to meet the needs of different packaging scenarios.

Widely used: A19 pneumatic plastic steel belt baler can be widely used in brick factory, aluminum, cotton mill, logistics and other fields, whether it is the fixing of large items, or the packaging of small goods, it can be easily dealt with, providing convenient and efficient packaging operations for you.

Hot melt free buckle design: The use of advanced hot melt free buckle technology, without the use of traditional metal buckle, you can realize the close connection of the packaging belt, not only improve the packaging efficiency, but also reduce the cost, more environmental protection and energy saving.

Choose A19 pneumatic plastic steel belt baler to make your packing operation easier, more efficient and environmentally friendly!

Applicable Strapping Tape Width	13-19mm
Applicable Strapping Tape Thickness	0.5-1.5mm

Our Product Introduction

for more products please visit us on setupack.com

Air Pressure	0.5-0.8Mpa
Applicable straps Type	PET/PP Straps
Enter Strap Modle	Divided up and down
Strap Sealing Form	Friction Welding
Maximum Binding Force	3500N
Net Weight(N.W.)	3.8kg
Size	280*160*180mm



Anhui Zhuoyu Industrial Manufacture Co., Ltd.



setupack.com

Room 101, 1st Floor, Building A3, Innovation industrial Park, 800 Wangjiang WestRoad, High-tech Zone, Hefei, Anhui, China.