₫

more products please

visit us on setuopack.com

# B19 Handheld PET Plastic Steel Belt Pneumatic Strapping Machine High Tension 3500N No Need For Up And Down Tape.

#### **Basic Information**

• Place of Origin: . Brand Name: Zhuoyu Certification: CF Model Number: R19 Minimum Order Quantity: 1 stage Price: To be discussed Packaging Details: 370\*225\*200mm • Delivery Time: 10-15 work days

• Payment Terms: MoneyGram, Western Union, T/T, D/P, D/A,

100+box+10days . Supply Ability:

**Product Specification** 

• Applicable Strapping Tape 13-19mm

• Applicable Strapping Tape 0.5-1.5mm

• Air Pressure: 0.5-0.8Mpa Applicable Straps Type: PET Straps • Enter Strap Modle: Free Tape Strap Sealing Form: Friction Welding Maximum Binding Force: 3500N Net Weight(N.W.):

280\*160\*180mm • Size:

• Highlight: High Tension Pneumatic Strapping Machine,

3500N Pneumatic Strapping Machine, Handheld Pneumatic Strapping Machine





### More Images







## Product Description

#### B19 Handheld PET pneumatic strapping machine

With its excellent performance and wide range of applications, the B19 pneumatic plastic steel belt baler is the ideal assistant for your packing operations.

Plastic steel belt applicability: suitable for the width between 13-19mm, thickness in the range of 0.5-1.5mm plastic steel belt, to provide you with a variety of choice space to meet different packaging needs.

No need for upper and lower subdivision: B19 pneumatic plastic steel belt baler does not need manual upper and

lower subdivision, simplifying the operation process and improving the packaging efficiency. High tensile design: The machine has a strong pulling force of 3500N, which can easily cope with the packaging

needs of various heavy items, ensuring the firmness and stability of the packaging.

Widely used: This machine can be widely used in logistics, warehousing, manufacturing and other fields, whether it is the fixing of large items, or the packaging of small goods, it can be easily dealt with, providing convenient and efficient packaging operations for you.

Hot melt free buckle design: The use of advanced hot melt free buckle technology, without the use of traditional metal or plastic buckle, you can realize the close connection of the packaging belt, not only improve the packaging efficiency, but also reduce the cost, more environmental protection and energy saving.

Choose B19 pneumatic plastic steel belt baler to make your packing operation easier, more efficient and

convenient!

Applicable Strapping Tape Width	13-19mm
Applicable Strapping Tape Tickness	0.5-1.5mm

Air Pressure	0.5-0.8Mpa
Applicable straps Type	PET/PP Straps
Enter Strap Modle	Free Tape
Strap Sealing Form	Friction Welding
Maximum Binding Force	3500N
Net Weight(N.W.)	3.8kg
Size	280*160*180mm



**2** 2ниочи Anhui Zhuoyu Industrial Manufacture Co., Ltd.







setuopack.com

Room 101, 1st Floor, Building A3, Innovation industrial Park, 800 Wangjiang WestRoad, High-tech Zone, Hefei, Anhui, China.