

MH-DM-95 Efficient Automatic Baler Dual Motor Running Stable Binding Firmly Control Panel

Our Product Introduction

for more products please visit us on setupack.com

Basic Information

- Place of Origin: China
- Brand Name: Zhuoyu
- Certification: CE
- Model Number: MH-DM-95
- Minimum Order Quantity: 1 stage
- Price: To be discussed
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 100 box per 10days



Product Specification

- Power: AC100-220V 50/60Hz 0.25kW
- Packing Speed: 3 Seconds/strap
- Tension Range: 5-50kg
- Workingtable Height: 750mm
- Applicable Straps Type: PP Strap
- Pp Strap Specification: Width 6~15mm,thickness 0.5-0.85mm
- PP Strap Spool: Inner Dia.200-210mm Outer Dia.400-450mm
- Machine Dimension: L785mmxW545mmxH750mm
- Highlight: control panel automatic baler,
Efficient automatic baler,
dual motor automatic baler



More Images



Product Description

Semi-automatic baler

Automatic baler - Efficient, stable and easy to use packaging solution.

Efficient, stable and easy to use, this automatic baler is an indispensable packaging tool for modern enterprises. Its operation is simple, one-click start, without complex Settings, you can quickly enter the working state.

In terms of speed, the baler performs well, and the packing takes only 3 seconds, which greatly improves the work efficiency. At the same time, the load-bearing capacity is strong, and it can cope with various heavyweight items to ensure the firmness and safety of the packaging.

The double motor design is another highlight of the baler, which has strong and stable power and ensures the lasting operation of the equipment.

The control panel design is humanized, and the functions are clear at a glance, which is convenient for users to monitor and adjust in real time.

Whether it is used in logistics, warehousing or manufacturing, this automatic baler can provide excellent packaging results, making your packaging work easier and more efficient.

Model number	MH-DM-95
--------------	----------

Our Product Introduction

for more products please visit us on setuopack.com

Power	AC100-220V,50/60Hz,0.25kW
Packing speed	3 seconds/strap
Tension range	5-50kg
Workingtable height	750mm
Applicable straps Type	PP strap
pp strap specification	width 6~15mm,thickness 0.5-0.85mm
PP strap spool	inner dia.200-210mm outer dia.400-450mm
Machine dimension	L785mmxW545mmxH750mm
Weight	55kg



**Anhui Zhuoyu Industrial
Manufacture Co., Ltd.**



setuopack.com

Room 101, 1st Floor,
Building A3, Innovation
industrial Park, 800
Wangjiang WestRoad,
High-tech Zone, Hefei,
Anhui, China.