₫

more products please

visit us on setuopack.com

# High Platform Intelligent Automatic Baler, Double Motor Fast Carton Baler Hot **Melt PP Plastic**

### **Basic Information**

• Place of Origin: • Brand Name: Zhuoyu Certification: CE Model Number: MH-DM-92 Minimum Order Quantity: 1 stage Price: To be discussed

 Payment Terms: L/C, D/A, D/P, T/T, Western Union,

MoneyGram

• Supply Ability: 100 box per 10days



# **Product Specification**

AC100-220V 50/60Hz 0.25kW • Power:

3 Seconds/strap • Packing Speed: • Tension Range: 5-50kg Workingtable Height: 750mm Applicable Straps Type: PP Strap

 Pp Strap Specification: Width 6~15mm.thickness 0.5-0.85mm PP Strap Spool: Inner Dia, 200-210mm Outer Dia, 400-450mm

 Machine Dimension: L785mmxW545mmxH750mm

Highlight: High Platform Automatic Baler, PP Plastic Automatic Baler, Double Motor Automatic Baler



## More Images





## Product Description

# Semi-automatic baler

### I. Product overview

Gaotai Intelligent automatic baler is a device designed for efficient and automated packaging. It integrates intelligent control, efficient operation and durability, and is suitable for packaging needs of various items such as express cartons, food and industrial products.

Two, the main characteristics

Wide range of adaptability:
Whether it is delivery cartons, food packaging, or other items of various shapes and sizes, Gaotai Intelligent automatic baler can easily cope with the perfect packaging solution. Fast and efficient:

The packing speed is extremely fast, and each packing only takes less than 3 seconds, which greatly improves the work efficiency and reduces the time and cost of manual operation.

Stainless steel, wear-resistant and rust-proof: The main body of the equipment is made of high-quality stainless steel, with excellent wear resistance and rust resistance, to ensure that the equipment maintains excellent performance and appearance in long-term use.

Applicable pp packing belt: Support the use of pp packaging belt, the specification broadband is 6-15mm, thick belt is 0.5-0.85mm, can be selected according to the packaging needs of different items suitable packaging belt specifications. Strong load-bearing capacity:

The load-bearing capacity of the equipment is strong, and it can easily cope with the packaging needs of various heavyweight items, ensuring the firmness and safety of the packaging.

Dual motor design:
The use of dual motor design, strong power, to ensure the lasting operation and efficient work of the equipment, even in the case of continuous work for a long time can maintain excellent performance.
Intelligent Control Panel:
The equipment is equipped with intelligent control panel, easy to operate, intuitive and easy to understand. At the same time, the control panel also has fault alarm and self-protection functions to ensure that the equipment can be stopped in time and issue alarms in abnormal situations.

Model number	MH-DM-92				
Power	AC100-220V,50/60Hz,0.25kW				
Packing speed	3 seconds/strap	ZHUOYU		hui Zhuoyu In	
Tension range	5-50kg		IVIa	nufacture Co.	, Lta.
Workingtable height	750mm	Room 101, 1s	t Floor	setuopack.com	
Applicable straps Type	PP strap	Building A3, In industrial Pa	novation		
pp strap specification	width 6~15mm,thickness 0.5-0.85mm	Wangjiang We High-tech Zon	e, Hefei,		
PP strap spool	inner dia.200-210mm outer dia.400-450mm	Anhui, Ch	ina.		
Machine dimension	L785mmxW545mmxH750mm				
Weight	55kg	1			