₫

more products please visit us on setuopack.com

MH-SDM-90 Automatic baler double motor hot melt carton packing and strapping machine

Basic Information

• Place of Origin: . Brand Name: Zhuoyu Certification: CE MH-SDM-90 Model Number:

• Minimum Order Quantity: 1 stage Price: To be discussed

 Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram

• Supply Ability: 100 box per 10days



Product Specification

AC100-220V 50/60Hz 0.25kW • Power:

3 Seconds/strap • Packing Speed: • Tension Range: 5-50kg Workingtable Height: 750mm Applicable Straps Type: PP Strap

 Pp Strap Specification: Width 6~15mm.thickness 0.5-0.85mm PP Strap Spool: Inner Dia, 200-210mm Outer Dia, 400-450mm

 Machine Dimension: L785mmxW545mmxH750mm

Highlight: Double Motor Carton Packing Machine,

Hot Melt Carton Packing Machine, Double Motor Automatic baler



More Images



Product Description

Semi-automatic baler

The packaging speed of this product is fast, and each route takes less than 3 seconds, making the tedious packing work easy

It is equipped with a powerful dual motor system to provide long-lasting and stable power output, ensuring a smooth packaging

process.

For a wide range of applications, whether it is daily packaging, logistics warehousing or industrial production, this baler can be perfectly competent to meet diverse needs.
Supports 24 hours of uninterrupted work, providing continuous and efficient support for your packaging tasks.

Equipped with advanced control panel, easy and intuitive operation, so that you can easily grasp the packaging progress and machine status, improve work efficiency.

This efficient 2nd generation dual motor semi-automatic baler, with its superior performance and convenient operation, will bring you unprecedented ease of packing experience!

| Model number | MH-SDM-90 | | |
|---------------------|---------------------------|--------------------------|--|
| Power | AC100-220V,50/60Hz,0.25kW | | |
| Packing speed | 3 seconds/strap | ZHUOYU Malar Balakara | Anhui Zhuoyu Industrial Manufacture Co., Ltd. |
| Tension range | 5-50kg | 0 0 | e setuopack.com |
| Workingtable height | 750mm | Room 101, 1st I | • |
| | | 1 | , |

| | Ξ | ₹ |
|---|-------|----|
| | È | ₹ |
| | - | ٠ |
| | Ξ | 3 |
| | C |) |
| | ā | ₹ |
| | ٠, | 1 |
| | C | 3 |
| | 7 | ₹ |
| | ≽ | ί |
| | ₹ | = |
| | 7 | 5 |
| | è | ź |
| | v | , |
| ۰ | τ | 3 |
| | ä | 5 |
| | ä | ۲ |
| | ñ | ĭ |
| | ă | ó |
| | С | |
| | 5 | 1 |
| | Q | 2 |
| | - | ۰ |
| | c | Ξ |
| | on uo | 0 |
| | c | 2 |
| | Ξ | 3 |
| | d | 'n |
| | ă | ń |
| | Ë | 9 |
| | ۶ | = |
| | ٥ | 4 |
| | × | ₹ |
| | × | ۲ |
| | > | ć |
| | ٤ | ľ |
| | ۶ | 3 |
| | ٤ | 2 |
| | Ξ | 3 |
| | | |
| | | |

| Applicable straps Type | PP strap |
|------------------------|---|
| pp strap specification | width 6~15mm,thickness 0.5-0.85mm |
| PP strap spool | inner dia.200-210mm outer dia.400-450mm |
| Machine dimension | L785mmxW545mmxH750mm |
| Weight | 90kg |

Building A3, Innovation industrial Park, 800 Wangjiang WestRoad, High-tech Zone, Hefei, Anhui, China.