₫

Automatic Baler Double Motor Hot-Melt Plastic Packaging And Carton Electric Strapping Machine

Basic Information

Place of Origin: ChinaBrand Name: ZhuoyuCertification: CE

Model Number: MH-SDML-90
 Minimum Order Quantity: 1 stage
 Price: To be discussed.

• Payment Terms: L/C, D/A, D/P, T/T, Western Union,

MoneyGram
Supply Ability: 100 box per 10days



Product Specification

• Power: AC100-220V 50/60Hz 0.25kW

Packing Speed: 3 Seconds/strap
Tension Range: 5-50kg
Workingtable Height: 450mm
Applicable Straps Type: PP Strap

• Pp Strap Specification: Width 6~15mm,thickness 0.5-0.85mm

PP Strap Spool: Inner Dia.200-210mm Outer Dia.400-450mm
 Machine Dimension: L71455mmxW545mmxH450mm

Highlight: Hot Melt Strapping Machine,
 Double Motor Strapping Machine,
 Electric Strapping Machine



More Images





Product Description

Semi-automatic baler

This product supports a variety of specifications of PP packaging tape, width between 5-15.5mm, thickness between 0.5-0.85mm.

This baler can easily complete a precise and efficient packing in just 1.5 seconds.

This baler is equipped with a premium dual motor to ensure the stability and durability of the machine.

Its control panel is designed to be simple and clear, and the various functions are clear at a glance. You can easily get started and quickly learn how to do it, so that you can complete the packaging work more efficiently.

This baler also has excellent efficiency and stability, which can work continuously for 24 hours without burning the machine. This baler is very versatile and can be used in a variety of occasions that need to be packed. Whether it is logistics warehouse, manufacturing or other industries, it can provide you with excellent service.

To sum up, this baler is undoubtedly an excellent product that integrates efficiency, stability, durability and convenience. It will bring you a better packing experience and make you more comfortable at work.

Model number	MH-SDML-90
	1

₫
\neg
3
0
ਰ
o
prod
ă
뎚
ğ
ੲ
Φ
25
ŏ
<
S
VISIT US
Ξ
S
2
7
8
ř
ō
Ō
꼺
×
Ö
com
3

Power	AC100-220V,50/60Hz,0.25kW						
Packing speed 3 seconds/strap		ZHUOYU			Anhui Zhuoyu Industrial Manufacture Co., Ltd.		
Tension range	5-50kg	•	0	e	setuopack.com		
Workingtable height	450mm	Room 101, 1st Floor, Building A3, Innovation					
Applicable straps Type	PP strap		g A3, IIII strial Park iang Wes	k, 800			
pp strap specification	width 6~15mm,thickness 0.5-0.85mm	High-te	ech Zone hui, Chi	, Hefei,			
PP strap spool	inner dia.200-210mm outer dia.400-450mm						
Machine dimension	L1455mmxW545mmxH450mm						
Weight	65kg	1					