DD163 Handheld Electric Baler PET Plastic Steel Belt Large Tensile Force

Basic Information

. Place of Origin: . Brand Name: Zhuoyu Certification: CF Model Number: L-DD163 Minimum Order Quantity: 1 stage Price: To be discussed Packaging Details: 480*280*220mm • Delivery Time: 10-15 work days

• Payment Terms: L/C, D/A, D/P, T/T, Western Union,

MoneyGram

100+box+10days Supply Ability:



Product Specification

• Applicable Strapping Tape 12-16mm

• Applicable Strapping Tape PET 0.5-1.0mm PP 0.6-1.2mm

Tickness:

Applicable Straps Type: PET/PP

• Tension Speed: 225mm/s

Strapping Force: 600-4000N Adjustable

 Battery Voltage: 14.4V Battery Capacity: 4.0Ah

About 60 Minutes Charging Time:

Net Weight(N.W.): 3.8kg

 Package Size: 360*135*130mm

• Highlight: Large Tensile Force Handheld Electric Baler

4000N Handheld Electric Baler



More Images





Product Description

Handheld electric storage baler

The electric baler is an efficient, versatile packaging tool designed to meet a wide range of packaging needs. One of its most notable features is the strong adjustable pulling force, which can be accurately adjusted in the range of 600-4000N to ensure that goods of different materials and sizes can be firmly packed. This feature makes the electric baler widely used in logistics, warehousing, manufacturing and other fields.

The baler is compatible with the packaging belt of PET and PP two materials, the width of the belt is between 12-16mm, the

thickness of the PET belt is 0.5-1.0mm, and the PP belt is 0.6-1.2mm. This wide applicability means that users can choose the right packaging belt according to different packaging needs to achieve the best packaging effect.

The electric baler is also equipped with a high-capacity battery with a capacity of up to 4,000 mah. In the case of full charge, 400-500 packaging operations can be carried out continuously, which greatly improves the work efficiency. At the same time, the charging time is only 60 minutes, which is convenient and fast, ensuring the continuous use of the device. In terms of operation, the electric baler adopts an intuitive and easy to use control panel, and users can complete the tightening and cutting steps of the packing belt through simple operations. This design not only simplifies the operation process, but also reduces the difficulty of operation, so that even first-time users can quickly get started.

Overall, this electric baler is ideal for a variety of packaging scenarios with its strong, adjustable pull, wide range of applicability, efficient battery performance, and intuitive and easy-to-use control panel.

| width | 12-16mm |
|-------|---------|
| | |

| Thickness | PET:0.5-1.0mm PP:0.6-1.2mm |
|----------------------|----------------------------|
| Appcable Straps Type | PET/PP |
| Speed | 225mm/s |
| · | |
| Strapping Force | 600-4000N |
| Battary Voltage | 14.4V |
| Battery Capacity | 4.0Ah |
| Charging time | About 60 Minutes |
| Net weight (n.w.) | 3.8kg(Battery included) |



Anhui Zhuoyu Industrial Manufacture Co., Ltd.







setuopack.com

Room 101, 1st Floor, Building A3, Innovation industrial Park, 800 Wangjiang WestRoad, High-tech Zone, Hefei, Anhui, China.