₫

MH-SDML-92 Semi-Automatic Baling Machine PP Packaging Express Carton **Packaging**

Basic Information

• Place of Origin: . Brand Name: Zhuoyu Certification: CF

MH-SDML-92 Model Number: Minimum Order Quantity: 1 stage Price: To be discussed

 Payment Terms: L/C, D/A, D/P, T/T, Western Union,

MoneyGram

• Supply Ability: 100 box per 10days



Product Specification

• Power: AC100-220V 50/60Hz 0.25kW

• Packing Speed: 3 Seconds/strap 5-50kg . Tension Range: Workingtable Height: 450mm Applicable Straps Type: PP Stran

 Pp Strap Specification: Width 6~15mm.thickness 0.5-0.85mm

 PP Strap Spool: Inner Dia.200-210mm Outer Dia.400-450mm Machine Dimension: L71455mmxW545mmxH450mm

• Highlight: Semi-Automatic Baling Machine,

Express Carton Packaging Baling Machine
PP Packaging Baling Machine



More Images



Product Description

Semi-automatic baler

The semi-automatic strapping machine is an efficient, versatile packaging device designed to meet a wide range of packaging needs. This machine is especially suitable for PP packaging tape, its compatible packaging tape width range is wide, from 6mm to 15mm can be applied, the thickness is supported by 0.5mm to 0.85mm packaging tape, providing users with great choice flexibility and convenience.

In terms of strapping speed, the semi-automatic strapping machine performs well, with each strapping taking only 3 seconds, greatly improving work efficiency, especially for scenarios requiring a large number of packaging operations. This feature makes the machine have a wide range of applications in the fields of warehouse management, food packaging, logistics and transportation, and can significantly improve the productivity and operational efficiency of enterprises.

In terms of operation, the machine is equipped with a simple and intuitive operation panel, and users can easily get started without complicated training. A series of actions such as loading, tensioning, cutting and gluing can be completed by simple button operation, which greatly simplifies the operation process and reduces the difficulty of operation.

In addition, the use of semi-automatic bundling machine is very wide. In the field of warehousing, it can effectively fix and protect various types of items, preventing displacement or damage during storage and transportation. In the food packaging industry, it can ensure the hygiene and safety of food, while improving the overall beauty of the product. In the field of logistics, semi-automatic bundling machine is an indispensable tool, it can help logistics enterprises quickly and accurately complete the

packaging and fixing of goods, to ensure the stability and safety of goods in the transport process. In short, this semi-automatic strapping machine is the ideal choice for packaging operations in many industries due to its efficiency, versatility and ease of operation.

| for more products please vi |
|-----------------------------|
| more products please |
| more products please vi |
| nore products please vi |
| ore products please vi |
| e products please vi |
| products please vi |
| roducts please vi |
| ducts please vi |
| lucts please vi |
| cts please vi |
| 's please vi |
| please vi |
| lease vi |
| ase vi |
| ISE V |
| Ф ≤. |
| ≤. |
| |
| Sit |
| ₹ |
| S |
| S |
| 윽 |
| ۔ |
| Š |
| 뽀 |
| ⊆ |
| Զ |
| ് |
| ดี |
| ᅎ |
| O |
| 으 |
| 3 |

| Model number | MH-SDML-92 | | | | |
|------------------------|---|----------|--|-------|--------------------|
| Power | AC100-220V,50/60Hz,0.25kW | | ZHUOYU | | nui Zhuoyu Indust |
| Packing speed | 3 seconds/strap | | | Mar | nufacture Co., Ltd |
| Tension range | 5-50kg | Boom 1 | m 101, 1st Floor | Eloor | setuopack.com |
| Workingtable height | 450mm | Building | ng A3, Innovation strial Park, 800 ijiang WestRoad, tech Zone, Hefei, | | |
| Applicable straps Type | PP strap | High-tec | | | |
| pp strap specification | width 6~15mm,thickness 0.5-0.85mm | Anh | nui, China | а. | |
| PP strap spool | inner dia.200-210mm outer dia.400-450mm | | | | |
| Machine dimension | L1455mmxW545mmxH450mm | | | | |
| Weight | 65kg | | | | |