₫

MH-TDM-00 Strapping Belt Tightening Hot Melt Integrated Automatic Baling **Machine**

Basic Information

• Place of Origin: . Brand Name: Zhuoyu Certification: CE Model Number: MH-TDM-00

 Minimum Order Quantity: 1 stage Price: To be discussed

 Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram

• Supply Ability: 100 box per 10days



Product Specification

• Power: AC100-220V 50/60Hz 0.25kW

• Packing Speed: 3 Seconds/strap 5-40kg . Tension Range: Workingtable Height: 750mm Applicable Straps Type: PP Stran

 Pp Strap Specification: Width 6~15mm.thickness 0.5-0.85mm PP Strap Spool: Inner Dia.200-210mm Outer Dia.400-450mm

 Machine Dimension: L785mmxW545mmxH750mm • Highlight: Hot Melt Baling Machine, Integrated Baling Machine Automatic Baling Machine



More Images



Product Description

Semi-automatic baler

The semi-automatic strapping machine is an advanced device designed to meet the diverse packaging needs, and its outstanding performance and wide range of application areas make it a popular choice in the market. This machine is especially suitable for PP packing tape, compatible packing tape width range between 6 to 15 mm, thickness between 0.5 to 0.85 mm, this wide compatibility provides great convenience for users.

In terms of strapping speed, the semi-automatic strapping machine performs well, with each strapping taking only 3 seconds, greatly improving work efficiency. This feature makes it easy to handle a large number of packaging tasks, whether it is warehouse management, food processing or logistics distribution, can complete a large number of packaging work in a short

The operation interface is simple and clear, the button layout on the simple operation panel is reasonable, the function logo is clear, and the user can easily get started without complicated training. This humanized design not only improves the ease of operation, but also reduces the failure rate caused by misoperation.

The machine also has a strong binding force, which can be adjusted between 5 and 40 kg according to actual needs, to ensure

that the packaging effect is firm and reliable. At the same time, the worktop height is designed to be 750 mm, which is ergonomic, making the operation more comfortable and labor-saving. In addition, the use of semi-automatic bundling machine is very wide. In the field of warehousing, it can effectively fix and

protect all kinds of goods; In the food processing industry, it can ensure food hygiene and safety; In terms of logistics distribution, semi-automatic bundling machine has played a huge role in helping logistics enterprises to quickly and accurately complete the packaging and fixing of goods.
In short, this semi-automatic strapping machine, with its excellent performance, wide range of applications and user-friendly

design, is the ideal choice for packaging operations in many industries.

₫
×
3
윽
Φ
헏
Ö.
ᆮ
ದ
S
₫
क़
S
Ö
≤.
<u>s</u>
Ξ
S
Q
~
æ
Ź
ᅙ
င္ထ
ದ
ኟ
읔
ã.

Model number	MH-TDM-00					
Power	AC100-220V,50/60Hz,0.25kW					
Packing speed	3 seconds/strap	ZHUOYU		Anhui Zhuoyu Industr Manufacture Co., Ltd.		
Tension range	5-40kg			Iviai		Lta.
Workingtable height	750mm	Boom :	Room 101, 1st F	Floor	setuopack.com	1
Applicable straps Type	PP strap	Building	A3, Inno	ovation		
pp strap specification	width 6~15mm,thickness 0.5-0.85mm	High-ted	Wangjiang WestRoad, High-tech Zone, Hefei,			
PP strap spool	inner dia.200-210mm outer dia.400-450mm		hui, Chin	a.		
Machine dimension	L785mmxW545mmxH750mm					
Weight	65kg	7				