MH-TDM-96 Blue Double Motor Automatic Hot Melt Carton Strapping Machine PP Packing Belt

Basic Information

Place of Origin: China
Brand Name: Zhuoyu
Certification: CE
Model Number: MH-TDM-96
Minimum Order Quantity: 1 stage

Minimum Order Quantity: 1 stagePrice: To be discussed

• Payment Terms: L/C, D/A, D/P, T/T, Western Union,

MoneyGram

• Supply Ability: 100 box per 10days



Product Specification

Power: AC100-220V 50/60Hz 0.25kW

Packing Speed: 3 Seconds/strap
Tension Range: 5-40kg
Workingtable Height: 750mm
Applicable Straps Type: PP Strap

Pp Strap Specification: Width 6~15mm,thickness 0.5-0.85mm
 PP Strap Specification: Inner Dia.160-190mm Outer Dia.200-210mm

Machine Dimension: L785mmxW545mmxH750mm

Blue Automatic Strapping Machine, PP Packing Belt Automatic Strapping Machine, Double Motor Automatic Strapping Machine



More Images

• Highlight:



Product Description

Semi-automatic baler

Semi-automatic bundling machine is an advanced equipment designed to meet the packaging needs of modern industrial and commercial fields. It is widely used in PP packaging belts and can easily cope with a wide range of packaging belts between 6mm and 15mm and a thickness between 0.5mm and 0.85mm, providing users with great flexibility and convenience. This strapping machine performs well in the strapping speed, each strapping only takes 3 seconds, which greatly improves the work efficiency, especially when dealing with a large number of packaging tasks, which can significantly shorten the working time and reduce labor costs.

The operation interface design is simple and intuitive, the button layout on the simple operation panel is reasonable, and the logo is clear, so that users can quickly get started without complicated training. This design not only improves the ease of operation, but also greatly reduces the failure rate caused by misoperation, providing users with a more stable and reliable packaging experience.

In terms of strapping force, the semi-automatic strapping machine has a strong adjustment ability, which can be flexibly adjusted between 5kg and 40kg according to actual needs, ensuring that the packaging effect is firm and reliable. At the same time, the height of the work surface is designed to be 750mm, which is in line with the ergonomic principle, so that the user can maintain a comfortable posture during the operation and effectively require fatigue.

maintain a comfortable posture during the operation and effectively reduce fatigue. In addition, the application field of semi-automatic bundling machine is very wide. In the field of warehousing, it can effectively fix and protect various types of items, preventing damage or displacement during storage and transportation. In the food processing industry, it can ensure food hygiene and safety, while improving the overall beauty of the product and market competitiveness. In terms of logistics distribution, it plays an irreplaceable role in helping logistics enterprises to quickly and accurately complete the packaging and fixing of goods, improving transportation efficiency and customer satisfaction. To sum up, this semi-automatic bundling machine with its high efficiency, stability, easy operation and a wide range of application fields and other characteristics, has become the first choice for packaging operations in many industries. It can not

only improve work efficiency and packaging quality, but also reduce labor costs and operating costs, creating greater economic benefits for enterprises.

Model number	MH-TDM-96			
Power	AC100-220V,50/60Hz,0.25kW			
Packing speed	3 seconds/strap	ZHUOYU	Anhui Zhuoyu Industrial Manufacture Co., Ltd.	
Tension range	5-40kg			
Workingtable height	750mm	Room 101, 1st Floor,		
Applicable straps Type	PP strap	Building A3, Innovation industrial Park, 800		
pp strap specification	width 6~15mm,thickness 0.5-0.85mm	Wangjiang Wes High-tech Zone, Anhui, Chir	, Hefei,	
PP strap spool	inner dia.160-190mm outer dia.200-210mm	Armui, Chir	ia.	
Machine dimension	L785mmxW545mmxH750mm			
Weight	65kg]		