

6-15mm Width 0.5-0.85mm Thickness Semi-automatic Strapping Machine Customized Packing

Our Product Introduction

for more products please visit us on setuopack.com

Basic Information

- Place of Origin: China
- Brand Name: Zhuoyu
- Certification: CE
- Model Number: Semi-automatic strapping machine
- Minimum Order Quantity: 1 stage
- Price: To be discussed
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 100 box per 10days



Product Specification

- Power: AC100-220V 50/60Hz 0.4kW
- Packing Speed: 3 Seconds/strap
- Tension Range: 5-40kg
- Workingtable Height: 750mm
- Applicable Straps Type: PP Strap
- Pp Strap Specification: Width6~15mm,thickness 0.5-0.85mm
- PP Strap Spool: Inner Dia.160-190mm Outer Dia.200-210mm
- Machine Dimension: L785mmxW545mmxH750mm
- Highlight: Semi-automatic Strapping Machine, Customized Packing Strapping Machine, 0.85mm Thickness Strapping Machine



More Images



Product Description

Semi-automatic baler

This low table semi-automatic strapping machine is a practical tool designed for handling heavy loads. It supports PP packing belts with widths between 5-15.5mm and thicknesses between 0.5-0.85mm, with bundling speeds up to 3 seconds/channel, which greatly improves work efficiency.

This machine adopts simple operation panel design, intuitive and easy to understand, so that you can easily get started. Whether it is warehousing, food packaging or logistics, this semi-automatic strapping machine can play an outstanding role. Its wide range of uses and powerful features make it easy for you to cope with various packaging needs in different situations. In addition, the machine has excellent durability and stable and reliable performance. It is made of high quality materials, durable and not easily damaged. At the same time, it also has good heat dissipation performance to ensure that long-term work can be stable. Overall, this low stage semi-automatic strapping machine is a useful aid in your work.

Model number	Semi-automatic strapping machine
Power	AC100-220V,50/60Hz,0.4kW
Packing speed	3 seconds/strap
Tension range	5-40kg
Workingtable height	750mm

for more products please visit us on setupack.com

Applicable straps Type	PP strap
pp strap specification	width 6~15mm,thickness 0.5-0.85mm
PP strap spool	inner dia.160-190mm outer dia.200-210mm
Machine dimension	L785mmxW545mmxH750mm
Weight	65kg

industrial Park, 800
Wangjiang WestRoad,
High-tech Zone, Hefei,
Anhui, China.