

Versatile Pneumatic Strapping Tool for PET and PP Material Packaging Solutions

Our Product Introduction

for more products please visit us on setupack.com

Basic Information

- Place of Origin: China
- Brand Name: Zhuoyu
- Certification: CE
- Model Number: L-X19
- Minimum Order Quantity: 1 stage
- Price: To be discussed
- Packaging Details: 38.5*23*21CM
- Delivery Time: 10-15 work days
- Payment Terms: MoneyGram, Western Union, T/T, D/P, D/A, L/C
- Supply Ability: 100+box+10days



Product Specification

- Model: L-X19
- Applicable Strapping Tape Width: 13-19mm
- Applicable Strapping Tape Thickness: 0.5-1.5mm
- Air Pressure: 0.5-0.8Mpa
- Applicable Straps Type: PET/PP Straps
- Enter Strap Mode: Divided Up And Down
- Strap Sealing Form: Friction Welding
- Maximum Binding Force: 3500N
- Net Weight(N.W.): 3.8kg
- Size: 280*160*180mm
- Highlight: 3500N pneumatic plastic steel belt baler, Portable Plastic Steel Belt Baler



Product Description

X19 Pneumatic plastic steel belt baler

Pneumatic baler, as an efficient and convenient packaging tool, its detailed features are as follows:

Designed for PET and PP packaging belts, this pneumatic baler is compatible with belts ranging in width from 13mm to 19mm and in thickness from 0.4mm to 1.2mm, providing users with a variety of options to meet different packaging needs.

The device needs to be connected to an air pump compressor to drive, and its applicable air pressure range is set between 0.5-0.8Mpa. In order to ensure the efficiency of air pressure transmission, it is recommended to use a gas pipe with a diameter of 8-10mm for connection. This configuration ensures that the pneumatic baler can operate stably and efficiently during operation.

In the packing effect, the pneumatic baler shows excellent performance. With a pulling force of up to 3500N, it completes packing operations quickly and firmly. The friction hot melt packing method ensures that the connection of the packing belt is tight and not easy to loosen, which effectively improves the stability and safety of the packaging.

Our Product Introduction

Pneumatic baler has a wide range of applications. Whether it is the steel, aluminum and other industries that need to pack heavy goods, the paper industry, cotton mills and other areas that need to handle large amounts of lightweight items, or the logistics industry that requires extremely high packaging efficiency, it can provide excellent performance.

In addition, the pneumatic baler is equipped with a complete tool kit, so users can use it directly without purchasing additional accessories. This not only saves users time and costs, but also improves the convenience and efficiency of packaging operations.



In summary, the pneumatic baler with its efficient, convenient, multi-functional characteristics, has become an indispensable packaging tool in many industries.

Applicable Strapping Tape Width	13-19mm
Applicable Strapping Tape Thickness	0.5-1.5mm
Air Pressure	0.5-0.8Mpa
Applicable straps Type	PET/PP Straps
Enter Strap Modle	Divided up and down
Strap Sealing Form	Friction Welding
Maximum Binding Force	3500N
Net Weight(N.W.)	3.8kg
Size	280*160*180mm



Anhui Zhuoyou Industrial Manufacture Co., Ltd.



setuopack.com

Room 101, 1st Floor, Building A3, Innovation Industrial Park, 800 Wangjiang WestRoad, High-tech Zone, Hefei, Anhui, China.