

Pneumatic Strapping Tool for PET and PP Packaging Belt Width 16-25mm Thickness 0.5-1.5mm Air Pressure 0.5-0.8Mp

Our Product Introduction

for more products please visit us on setuopack.com

Basic Information

- Place of Origin: China
- Brand Name: Zhuoyu
- Certification: CE
- Model Number: L-X25
- Minimum Order Quantity: 1 stage
- Price: To be discussed
- Packaging Details: 38.5*23*21CM
- Delivery Time: 10-15 work days
- Payment Terms: MoneyGram, Western Union, T/T, D/P, D/A, L/C
- Supply Ability: 100+box+10days



Product Specification

- Model: L-X25
- Applicable Strapping Tape Width: 16-25mm
- Applicable Strapping Tape Thickness: 0.5-1.5mm
- Air Pressure: 0.5-0.8Mpa
- Applicable Straps Type: PET/PP Straps
- Enter Strap Mode: Divided Up And Down
- Strap Sealing Form: Friction Welding
- Maximum Binding Force: 3500N
- Net Weight(N.W.): 3.8kg
- Size: 280*160*180mm
- Highlight: 3500N pneumatic plastic steel belt baler, Portable Plastic Steel Belt Baler



Product Description

X25 Pneumatic plastic steel belt baler

The pneumatic baler is a powerful packaging device designed to meet a wide range of industrial and commercial packaging needs. The following is a detailed description of the product:

The pneumatic baler is widely applicable to the packaging belt of PET and PP, the width of the packaging belt is between 16-25mm, and the thickness is between 0.5-1.5mm. This design allows the baler to flexibly respond to different sizes and materials of the packaging belt, to meet diverse packaging needs.

In terms of power, the pneumatic baler needs to be connected to the air pump compressor to provide stable air pressure. Its applicable air pressure range is 0.5-0.8Mpa, in order to ensure the efficiency of air pressure transmission, it is recommended to use a diameter of 8-10mm to connect the air pipe. This configuration ensures that the baler can work continuously and efficiently.

The pneumatic baler has a strong pull force of 3500N, which can quickly and firmly complete the packing operation. The friction hot melt technology

Our Product Introduction

is used to make the packing belt tightly fused at the joint to ensure the stability and safety of the packaging. This technique not only improves the packing efficiency, but also reduces the risk of breaking the packing belt.

The pneumatic baler has a wide range of applications, suitable for paper industry, steel, aluminum, cotton mill, logistics and other industries. Whether it is in the industrial production field that requires high-strength packaging, or in the commercial environment that requires efficient packaging, it can play an excellent performance.

In addition, the pneumatic baler is equipped with a complete tool kit, including a baling belt cutter, tensioner, etc., so users can use it directly without purchasing additional accessories. This design not only improves the convenience of packaging operations, but also reduces the cost of users.

In summary, the pneumatic baler with its efficient, convenient, multi-functional characteristics, has become an indispensable packaging tool in many industries.

Applicable Strapping Tape Width	16-25mm
Applicable Strapping Tape Tickness	0.5-1.5mm
Air Pressure	0.5-0.8Mpa
Applicable straps Type	PET/PP Straps
Enter Strap Modle	Divided up and down
Strap Sealing Form	Friction Welding
Maximum Binding Force	3500N
Net Weight(N.W.)	3.8kg
Size	280*160*180mm



Anhui Zhuoyu Industrial Manufacture Co., Ltd.



setupack.com

Room 101, 1st Floor, Building A3, Innovation industrial Park, 800 Wangjiang WestRoad, High-tech Zone, Hefei, Anhui, China.