

## X25 Pneumatic Strapping Tool The Ultimate Packaging Solution for Industrial and Commercial Needs

Our Product Introduction

for more products please visit us on [setupack.com](http://setupack.com)

### Basic Information

- Place of Origin: China
- Brand Name: Zhuoyu
- Certification: CE
- Model Number: L-X25
- Minimum Order Quantity: 1 stage
- Price: To be discussed
- Packaging Details: 38.5\*23\*21CM
- Delivery Time: 10-15 work days
- Payment Terms: MoneyGram, Western Union, T/T, D/P, D/A, L/C
- Supply Ability: 100+box+10days



### Product Specification

- Model: L-X25
- Applicable Strapping Tape Width: 16-25mm
- Applicable Strapping Tape Thickness: 0.5-1.5mm
- Air Pressure: 0.5-0.8Mpa
- Applicable Straps Type: PET/PP Straps
- Enter Strap Mode: Divided Up And Down
- Strap Sealing Form: Friction Welding
- Maximum Binding Force: 3500N
- Net Weight(N.W.): 3.8kg
- Size: 280\*160\*180mm
- Highlight: 3500N pneumatic plastic steel belt baler, Portable Plastic Steel Belt Baler



### Product Description

## X25 Pneumatic plastic steel belt baler

The pneumatic baler is an efficient, versatile packaging device designed to meet a wide range of industrial and commercial packaging needs.

The following is a detailed description of the product:

The pneumatic baler is widely applicable to the packaging belt of PET and PP, the width of the packaging belt ranges from 16 to 25 mm, and the thickness is between 0.5 and 1.5 mm. The specially designed upper and lower packaging belt function makes the packing process more flexible and convenient, and can easily deal with a variety of complex and irregular packing items.

In terms of power, the pneumatic baler needs to be connected to the air pump compressor to provide stable air pressure. The applicable air pressure range is 0.5 to 0.8Mpa, and in order to ensure the efficiency of air pressure transmission, it is recommended to use 8 to 10 mm diameter of the air pipe connection. This configuration ensures that the baler can work continuously and efficiently to meet a variety of high-intensity packaging needs.

The pneumatic baler has a strong pull force of 3500N, which can quickly and firmly complete the packing operation. The friction hot melt technology

Our Product Introduction

is used, and the high temperature generated by friction melts the packaging belt and is closely connected together to ensure the stability and safety of the packaging.

The pneumatic baler has a wide range of applications, suitable for paper industry, steel, aluminum, cotton mill, logistics and other industries. Whether it is in the industrial production field that requires high-strength packaging, or in the commercial environment that requires efficient packaging, it can play an excellent performance.

In addition, the pneumatic baler is also equipped with a complete tool kit, including packaging belt cutter, tensioner, etc., to facilitate users to carry out packaging operations. These tools not only improve the convenience of packaging operations, but also reduce the user's operation difficulty and cost.

To sum up, the pneumatic baler has become an indispensable packaging tool in many industries with its high efficiency, multi-function and wide application fields.

Applicable Strapping Tape Width	16-25mm
Applicable Strapping Tape Thickness	0.5-1.5mm
Air Pressure	0.5-0.8Mpa
Applicable straps Type	PET/PP Straps
Enter Strap Modle	Divided up and down
Strap Sealing Form	Friction Welding
Maximum Binding Force	3500N
Net Weight(N.W.)	3.8kg
Size	280*160*180mm



Anhui Zhuoyu Industrial Manufacture Co., Ltd.



[setuopack.com](http://setuopack.com)

Room 101, 1st Floor, Building A3, Innovation industrial Park, 800 Wangjiang WestRoad, High-tech Zone, Hefei, Anhui, China.