

## Pneumatic Strapping Tool for High-Efficiency and Precise Spraying HIQ 4500C Gravity Spray Gun with Multiple Nozzle Options

Our Product Introduction

for more products please visit us on [setuopack.com](http://setuopack.com)

### Basic Information

- Place of Origin: China
- Brand Name: Zhuoyu
- Certification: CE
- Model Number: HIQ 4500C
- Minimum Order Quantity: 1 stage
- Price: To be discussed
- Delivery Time: 10-15 work days
- Payment Terms: MoneyGram, Western Union, T/T, D/P, D/A, L/C
- Supply Ability: 100+box+10days



### Product Specification

- Model: HIQ 4500C
- Standard Nozzle Optional Nozzle: 0.5mm 0.5/0.8/1.0mm
- Fluid Output: 80/110/120ml/min
- Operating Pressure: 1.0-2.5bar/01-0.25Mpa
- Pattern Width: 100-150mm
- Air Consumption: 9cfm/250L/min
- Paint Capacity: 250ml
- Color Box: 16x12.5x22.5cm

### Product Description

#### AIR SPRAY GU

The HIQ 4500C is a high-performance gravity spray gun, specially designed for fine spraying operations. It is suitable for scenarios that require high-precision coating, such as model painting, handicraft making, and surface treatment of electronic products. Its lightweight structure, adjustable spraying parameters and multi-specification nozzle options make it an ideal choice for professional artisans and DIY enthusiasts.

#### ✓ Gravity feeding system

The 250ml paint cup capacity ensures stable material supply, reduces frequent touch-up paint, and improves work efficiency. It is suitable for low to medium viscosity coatings, such as water-based paint, oil-based paint and varnish.

Multiple specifications of nozzles are available for selection

It comes standard with a 0.5mm fine nozzle, suitable for ultra-thin coatings and detailed processing.

Optional 0.8mm and 1.0mm nozzles are available to expand the spraying range and meet the requirements of different coating viscosities.

#### ✓ Low-pressure and high-efficiency spraying

Working pressure: 1.0-2.5bar (0.1-0.25Mpa), energy-saving and paint-saving, reducing overspray waste.

Uniform atomization, fine coating, and reduced sagging and orange peel phenomena.

#### ✓ Precise spraying control

The spray width is adjustable from 100 to 150mm, flexibly adapting to workpieces of different sizes.

The fluid output is 80-120 mL /min (adjusted according to the nozzle size), precisely controlling the coating flow rate.

#### ✓ Lightweight design

Compact structure, less likely to cause fatigue during long-term handheld operation.

The air consumption is only 9CFM (250L/min), and it is compatible with most small air compressors.

Our Product Introduction

for more products please visit us on [setuopack.com](http://setuopack.com)

Type of Feed	Gravity
Fluid Output	80/110/120ml/min
Operating Pressure	1.0-2.5bar/0.1-0.25Mpa
Pattern Width	100-150mm
Paint Capacity	250ml



**Anhui Zhuoyu Industrial Manufacture Co., Ltd.**



[setuopack.com](http://setuopack.com)

Room 101, 1st Floor, Building A3, Innovation industrial Park, 800 Wangjiang WestRoad, High-tech Zone, Hefei,  
Anhui, China.