

High-Performance Pneumatic Strapping Tool for Professional Spraying Technicians and Industrial Users

Our Product Introduction

for more products please visit us on setuopack.com

Basic Information

- Place of Origin: China
- Brand Name: Zhuoyu
- Certification: CE
- Model Number: T80
- Minimum Order Quantity: 1 stage
- Price: To be discussed
- Delivery Time: 10-15 work days
- Payment Terms: MoneyGram, Western Union, T/T, D/P, D/A, L/C
- Supply Ability: 100+box+10days



Product Specification

- Model: T80
- Standard Nozzle Optional Nozzle: 1.3mm 1.3/1.6 / 2.0mm
- Fluid Output: 250/300/350ml/min
- Operating Pressure: 1.5-4.0bar/ 0.15-0.4Mpa
- Pattern Width: 270-300mm
- Air Consumption: 9.8-10.6cfm/280-300L/min
- Paint Capacity: 600ml
- Color Box: 16x12.5x22.5cm

Product Description

AIR SPRAY GU

The T80 is a high-performance gravity spray gun, specifically designed for medium and large-scale spraying operations. It is suitable for scenarios such as automotive repair, furniture painting, and industrial equipment surface treatment that require high-efficiency and high-flow spraying. Its large-capacity paint cup, wide-range spraying capability and multi-specification nozzle options make it an ideal choice for professional spraying technicians and industrial users.

✓ Gravity feeding system

600ml large-capacity paint cup, reducing frequent touch-up paint and improving continuous operation efficiency.

It is suitable for medium to high viscosity coatings, such as primers, topcoats and high-solid content coatings.

Multiple specifications of nozzles are available for selection

Standard equipped with a 1.3mm nozzle to balance spraying efficiency and coating quality.

Optional 1.6mm and 2.0mm nozzles are available to meet the requirements of higher viscosity coatings and large-area spraying.

✓ High-pressure and high-efficiency spraying

The working pressure is 1.5-4.0bar (0.15-0.4Mpa) to ensure that the coating is fully atomized and enhance the adhesion of the coating.

Uniform atomization, smooth coating, and reduced orange peel and sagging phenomena.

✓ Wide-width spraying capability

The spray width is adjustable from 270 to 300mm, significantly enhancing the coverage efficiency and making it suitable for medium and large-sized workpieces.

The fluid output is 250-350ml/min (adjusted according to the nozzle size), meeting the high flow rate requirements.

✓ Industrial-grade durable design

Sturdy structure, suitable for long-term and high-intensity use.

Air consumption: 9.8-10.6CFM (280-300L/min), compatible with industrial-grade air compressors.

Our Product Introduction

for more products please visit us on setupack.com

Type of Feed	Gravity
Fluid Output	250/300/350ml/min
Operating Pressure	1.5-4.0bar/ 0.15-0.4Mpa
Pattern Width	270-300mm
Paint Capacity	600ml



Anhui Zhuoyu Industrial Manufacture Co., Ltd.



setupack.com

Room 101, 1st Floor, Building A3, Innovation industrial Park, 800 Wangjiang WestRoad, High-tech Zone, Hefei,
Anhui, China.